

TYPE SRC DIMENSIONS - inches (mm)

Size	A	B	C	D Acceptable Rod Size
SRC-1	1 3/8 (35)	1/2 x 1 3/4 Long (13 x 44 Long)	1 x 1 x 1/8 (25 x 25 x 3)	1/4 to 5/8 (6 to 16)
SRC-1 1/2	1 9/16 (40)	5/8 x (16 x Long)	1 1/2 x 1 1/2 x 1/4 (38 x 38 x 6)	to 1 to 25)
SRC-2	1 3/4 (44)	5/8 x 3 Long (16 x 76 Long)	2 x 2 x 1/4 (51 x 51 x 6)	7/8 to 1 1/4 (22 to 32)

TYPE SRC WITH STEEL ANGLE ASSEMBLY RATINGS

Rod Size in (mm)	Maximum Compr. Force lbs (kN)	Steel Angle Stiffener Min. Size in (mm)	Max. Length in (mm)	Maximum SRC Spacing in (mm)
1/4	75	1 x 1 x 1/8	96	14
3/8	425	1 x 1 x 1/8	96	22
1/2	1275	1 x 1 x 1/8	96	31
	1200	1 1/2 x 1 1/2 x 1/4	120	31
5/8	1475	1 x 1 x 1/8	96	39
	1325	1 1/2 x 1 1/2 x 1/4	120	39
3/4	2500	1 1/2 x 1 1/2 x 1/4	144	48
7/8	4600	1 1/2 x 1 1/2 x 1/4	132	56
	4400	2 x 2 x 1/4	144	56
1	5800	1 1/2 x 1 1/2 x 1/4	132	56

APPROVED

California Office of Statewide
Health Planning and Development

FIXED EQUIPMENT ANCHORAGE

OPA-0349

AUGUST 5, 2002



Bill Staehlin

Bill Staehlin (916) 654-3362

